

### Raychem

#### Product description

HVIS is an adhesive coated, heat-shrinkable sheet which provides insulation enhancement and protection against accidentally induced discharge. When heated the HVIS sheet shrinks in two directions to tightly conform to complex shapes.

A Raychem void-filling mastic, S1061, can be added to ensure that even protruding shapes are insulated. A Raychem sealing mastic, S1085, can also be applied to provide an environmentally sealed connection.

The sheet can be cut to size on site and loosely secured in place with clamps and brackets available from Raychem. Once installed, the clamps and brackets can be removed and re-used. HVIS sheet will provide flashover protection up to 17.5 kV or up to 25 kV if the void-filling mastic is applied underneath the sheet, or up to 36 kV if a double layer of HVIS is used.

Re-usable joint covers can also be made to allow access or maintenance when required.

#### Applications

HVIS sheet will cover almost any size or shape of busbar joint, making it ideal for insulating busbar tees, elbows and other connections where tubing and tape cannot be used.

#### Clearance reduction

The table below indicates the clearance reductions which are possible using HVIS sheet. These are derived from BIL, AC withstand, DC withstand and discharge extinction tests. These clearances should not be adopted without testing by the user. Sharp electrodes and unusual geometries may require wider clearances.

Rated voltage (kV)	Phase – phase (mm)	Phase – ground (mm)	IEC 71-2 air clearance (mm)
<b>Round busbars</b>			
12	55	65	120
17.5	70	85	160
24	95	125	220
36	150	205	320
<b>Rectangular busbars</b>			
12	65	75	120
17.5	85	104	160
24	115	150	220
36	200	285	320

#### HVIS

#### High voltage insulation sheets

Voltage class 36 kV

Max. busbar width 150 mm



#### Features/benefits

- Compatible with all other products in the Raychem MV insulation enhancement system
- Easy to install on site using a gas torch or hot air device
- Manufactured from a non-halogen based material, noxious and corrosive effects are greatly reduced in the event of a fire
- Excellent anti-tracking properties
- Excellent UV and weather resistant properties make HVIS suitable for indoor or outdoor use
- Can be stored indefinitely at temperatures up to 50°C without loss of performance

# HVIS


# High voltage insulation sheets

Key product specifications	Test method	Requirement
Dielectric strength	ASTM D149, IEC 243	130 kV/cm min. @ 2 mm
Accelerated ageing - Tensile strength - Ultimate elongation	ISO 188, ASTM D2671	168 hrs @ 120°C 10 MPa min. 300% min.
Low temperature flexibility	ASTM D2671 Procedure C	No cracking after 4 hrs @ -40°C
Comparative tracking index	VDE 0303/1	KA 3c
Smoke index	NES 711	Less than 50
Acid gas generation	Raychem PPS 3010 4.23	Less than 2% by weight
Resistance to transformer oil - Tensile strength - Ultimate elongation	VDE 0370	168 hrs @ 23°C 7.5 MPa min. 300% min.


**Note:** For further product specification information see Raychem PPS 3010/25. The above information refers to backing material only, for adhesive requirements see PPS 3012/43. For void-filling mastic S1061 requirements see PPS 3012/13, for sealing mastic S1085 requirements see PPS 3012/3.

## Product selection

For rectangular busbars max. thickness 15 mm



**T-connection**





**Flat elbow connection**

Busbar width	Cut size needed (mm)	No. of installations per		Cut size needed (mm)	No. of installations per	
		HVIS-05 sheet	HVIS-10 rolls		HVIS-05 sheet	HVIS-10 rolls
25	275 x 225	4	88	275 x 175	4	114
50	325 x 250	4	80	325 x 225	4	88
75	400 x 275	2	50	325 x 250	2	52
100	450 x 325	2	44	450 x 275	2	44
175	550 x 425	1	23	550 x 325	1	30

**Note:** This table should be used as a guideline only. Please experiment with one or two joints before adopting final cut size. The busbars are assumed to be insulated to 25 mm from the joint. Cut size should extend a minimum of 100 mm on each leg of the joint before shrinking and should overlap existing insulation by 65 mm after shrinking.

## Ordering information



Ordering description	Dimensions P a (m) nom.	Q a nom.	W <sub>1</sub> b min.	W <sub>2</sub> a min.	UOM
HVIS-05	0.5	660	1.5	2.4	sheet
HVIS-10	10.0	660	1.5	2.4	roll
S1061-8-300	0.3	60	-	-	piece
S1085-1-300	0.3	20	-	-	piece
HVIS-TOOLS-01 (basic clamp and bracket kit)					kit
HVIS-TOOLS-02 (extended clamp and bracket kit)					kit

**Note:** Dimensions in mm unless otherwise stated. a = as supplied b = after free recovery. Longitudinal and transverse change after free recovery: -25 % ±10%. Installation instructions EPP 0623 5/96 and Material Safety Data Sheet available on request. When required, typically one piece of sealing mastic, S1085, is applied on each leg of the joint and one or two pieces of void-filling mastic, S1061, used to cover uneven shapes.

## Technical reports

UVR 8114 – Qualification report for HVIS

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct and reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance of any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for these products is set forth in our standard terms and conditions of sale.

ALR, AMP, Cevolit, Cevosil, Critchley, Dorman Smith, Dulmison, Hellstern, La Prairie, Morlynn, Raychem, and SIMEL are trademarks of Tyco International Ltd.

**tyco**

Electronics

Energy Division



AMP

Cevolit

Cevosil



Hellstern



MORLYNN INSULATORS

Raychem

SIMEL

### Argentina

Phone: ++54-11-4733 2277  
Fax: ++54-11-4733 2267

### Australia

Phone: ++61-2-4390 1111  
Fax: ++61-2-4353 2497

### Brazil

Phone: ++55-11-861 1311  
Fax: ++55-11-861 1862

### Canada

Phone: ++1-905-475 6222  
Fax: ++1-905-470-4453

### France

Phone: ++33-3-80583200  
Fax: ++33-3-80341015

### Mexico

Phone: ++52-5-729 0405  
Fax: ++52-5-361-8545

### Thailand

Phone: ++66-2-7394026 - 32  
Fax: ++66-2-3260563 - 64

### United States of America

Phone: ++1-800-327-6996  
Fax: ++1-800-527-8350

## Tyco Electronics Raychem GmbH

Energy Division  
Haidgraben 6, 85521 Ottobrunn/Munich, Germany  
Phone: ++49-89-6089-0, Fax: ++49-89-6096345

<http://energy.tycoelectronics.com>